

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

IN THE CLAIMS:

- C'
Cont'd
1. (Previously Amended) An ink jet recording apparatus comprising:
 - an ink jet recording head having nozzle orifices from which inkdrops are ejected;
 - an ink storage unit for storing ink to be supplied to the recording head;
 - an ink flow passage communicating the ink storage unit and the recording head;
 - a valve unit for opening/closing the ink flow passage;
 - a capping unit for sealing the nozzle orifices, provided with an air hole communicating with the atmosphere;
 - an air valve for opening/closing the air hole;
 - a suction pump for reducing pressure in an internal space of the capping unit to discharge inkdrops from the nozzles when the capping unit seals the nozzle orifices; and
 - a control unit for controlling the valve unit, the capping unit and the suction pump in such order that:
 - the suction pump decompresses the internal space of the capping unit under a condition that the valve unit closes the ink flow passage and the capping unit seals the nozzle orifice; and
 - the valve unit opens the ink flow passage after a predetermined time period elapseswherein the air valve always closes the air hole while the suction pump decompresses the internal space of the capping unit.
 - 2-3. (Withdrawn).
 4. (Original) The ink jet recording apparatus as set forth in claim 1, wherein the predetermined time period is defined as either a time period required for obtaining a satisfactory deaeration degree of ink between the valve unit and the nozzle orifices, or a time period required for accumulating air bubbles therein.

5. (Currently Amended) An ink jet recording apparatus comprising:
- an ink jet recording head having nozzle orifices from which inkdrops are ejected;
 - an ink storage unit for storing ink to be supplied to the recording head;
 - an ink flow passage communicating the ink storage unit and the recording head;
 - a valve unit for opening/closing the ink flow passage;
 - a capping unit for sealing the nozzle orifices;
 - a suction pump for decompressing an internal space of the capping unit to discharge inkdrops from the nozzles when the capping unit seals the nozzle orifices; and
 - a control unit for controlling the valve unit, the capping unit and the suction pump in such order that:

the suction pump decompresses the internal space of the capping unit under a condition that the valve unit closes the ink flow passage and the capping unit seals the nozzle orifice;

the valve unit opens the ink flow passage after a first predetermined time period elapses since the starting of the decompressing by the suction pump; and }

the suction pump continues decompressing the internal space of the capping unit for a second predetermined time period after the opening of the ink flow passage; ~~wherein the controller controls the capping unit such that the decompressed state of the internal space of the capping unit is maintained while the suction pump is driven.~~

6-32. (Withdrawn).

33. (Previously Amended) The ink jet recording apparatus as set forth in any one of claims 1 and 5, wherein the valve unit includes:

- a valve control chamber which constitutes a part of the ink flow passage;
- a flexible diaphragm which constitute a bottom wall of the valve control chamber;

AMENDMENT UNDER 37 C.F.R. § 1.111
U.S. APPLICATION NO. 09/545,834
ATTORNEY DOCKET NO. Q58793

an actuation body for deforming a center portion of the diaphragm in a direction perpendicular thereto.

34. (Original) The ink jet recording apparatus as set forth in claim 33, wherein the valve control chamber has an entrance port formed on a top wall thereof at a portion where is away from the center portion of the diaphragm, and an exit port formed on the top wall at right above the center portion of the diaphragm.

35. (Original) The ink jet recording apparatus as set forth in claim 34, wherein the entrance port is arranged below the exit port.

C1
could
36. (Original) The ink jet recording apparatus as set forth in claim 34, wherein the circumferential portion of the exit port is tapered such that a diameter of the port is reduced toward the above.

37. (Original) The ink jet recording apparatus as set forth in claim 34, wherein the diaphragm includes an annular convex on the center portion thereof for sealing the exit port when the diaphragm is deformed by the actuation body.

38. (Original) The ink jet recording apparatus as set forth in claim 37, wherein an annular groove is formed so as to surround the exit port, against which the annular convex is to be abutted; and wherein an outer peripheral wall of the groove is tapered such that a diameter of thereof is reduced toward the above.

39. (Original) The ink jet recording apparatus as set forth in claim 38, wherein a distance between the annular convex and the annular groove is 1.0 - 1.3 mm when the ink flow passage is opened.

AMENDMENT UNDER 37 C.F.R. § 1.111
U.S. APPLICATION NO. 09/545,834
ATTORNEY DOCKET NO. Q58793

40. (Original) The ink jet recording apparatus as set forth in claim 34, wherein a cross sectional area of the ink flow passage between the exit port and the recording head becomes larger as further from the exit port.

41. (Original) The ink jet recording apparatus as set forth in claim 33, wherein the actuation body is a rod member arranged below the diaphragm.

42-65. (Withdrawn).

C1
Cont'd
66. (Previously Amended) A cleaning control method for an ink jet recording apparatus which comprises:

an ink jet recording head having nozzle orifices from which inkdrops are ejected;

an ink storage unit for storing ink to be supplied to the recording head; an ink flow passage communicating the ink storage unit and the recording head;

a valve unit for opening/closing the ink flow passage;

a capping unit for sealing the nozzle orifices, provided with an air hole communicating with atmosphere;

an air valve for opening/closing the air hole;

a suction pump for reducing pressure in an internal space of the capping unit to discharge inkdrops from the nozzles when the capping unit seals the nozzle orifices, the method comprising the steps of:

closing the air hole using the air valve;

sealing the nozzle orifices by the capping unit;

closing the ink flow passage by the valve unit;

driving the suction pump to decompress the internal space of the capping unit;

holding the decompressed state for a predetermined time period; and

opening the ink flow passage by the valve unit

AMENDMENT UNDER 37 C.F.R. § 1.111
U.S. APPLICATION NO. 09/545,834
ATTORNEY DOCKET NO. Q58793

wherein the air valve always closes the air hole while the suction pump decompresses the internal space of the capping unit.

67. (Original) The cleaning control method as set forth in claim 66, wherein the sealing step and the closing step are executed synchronously or exchangeably.

68. (Original) The cleaning control method as set forth in claim 66, wherein the predetermined time period is defined as either a time period required for obtaining a satisfactory deaeration degree of ink between the valve unit and the nozzle orifices, or a time period required for accumulating air bubbles therein.

69. (Currently Amended) A cleaning control method for an ink jet recording apparatus which comprises:

an ink jet recording head having nozzle orifices from which inkdrops are ejected;

an ink storage unit for storing ink to be supplied to the recording head;

an ink flow passage communicating the ink storage unit and the recording head;

a valve unit for opening/closing the ink flow passage;

a capping unit for sealing the nozzle orifices;

a suction pump for reducing pressure in an internal space of the capping unit to discharge inkdrops from the nozzles when the capping unit seals the nozzle orifices, the method comprising the steps of:

sealing the nozzle orifices by the capping unit;

closing the ink flow passage by the valve unit;

driving the suction pump to decompress the internal space of the capping unit;

holding the decompressed state for a first predetermined time period; and

opening the ink flow passage by the valve unit ~~while driving the suction pump~~ after the first predetermined period has elapsed; and

AMENDMENT UNDER 37 C.F.R. § 1.111
U.S. APPLICATION NO. 09/545,834
ATTORNEY DOCKET NO. Q58793

stopping the driving of the suction pump after a second predetermined time period has elapsed since the opening of the ink flow passage ~~wherein the decompressed state of the internal space of the capping unit is maintained while the suction pump is driven.~~

70. (Original) The cleaning control method as set forth in claim 69, wherein the sealing step and the closing step are executed synchronously or exchangeably.

71. (Cancelled).

72. (Original) The cleaning control method as set forth in claim 69, further comprises the step of driving the suction pump between the sealing step and the closing step.

73. (Original) The cleaning control method as set forth in claim 71, further comprises the step of driving the suction pump again after the stopping step has executed.

74. (Original) The cleaning control method as set forth in claim 73, further comprises the steps of:

releasing the capping unit from the nozzle orifices after the suction pump has driven again; and driving the suction pump again to discharge ink from the nozzle orifices in a capping released state.

75-79. (Withdrawn).

80. (Currently Amended) An ink jet recording apparatus comprising:

an ink jet recording head having nozzle orifices from which ink drops are ejected;
an ink storage unit for storing ink to be supplied to the recording head;
an ink flow passage communicating the ink storage unit and the recording head; and

AMENDMENT UNDER 37 C.F.R. § 1.111
U.S. APPLICATION NO. 09/545,834
ATTORNEY DOCKET NO. Q58793

a valve unit for opening/closing the ink flow passage, the valve unit including:

a valve control chamber which constitutes a part of the ink flow passage, the valve control chamber including an entrance port and an exit port;

a flexible diaphragm which ~~constitute~~ constitutes a bottom wall of the valve control chamber; and

an actuation body for deforming a center portion of the diaphragm ~~in a direction perpendicular thereto~~ so as to close only the exit port. ✓

C1
Cont'd
81. (Currently Amended) The ink jet recording apparatus as set forth in claim 80, wherein the ~~valve control chamber has an entrance port is formed on a top wall thereof of the valve control chamber~~ at a portion ~~where is~~ away from the center portion of the diaphragm, and ~~an the~~ exit port is ~~formed~~ on the top wall at right above the center portion of the diaphragm. ✓

82. (Previously Added) The ink jet recording apparatus as set forth in claim 81, wherein the entrance port is arranged below the exit port. ✓

83. (Previously Added) The ink jet recording apparatus as set forth in claim 81, wherein the circumferential portion of the exit port is tapered such that a diameter of the port is reduced toward the above. ✓

84. (Previously Added) The ink jet recording apparatus as set forth in claim 81, wherein the diaphragm includes an annular convex on the center portion thereof for sealing the exit port when the diaphragm is deformed by the actuation body. ○

85. (Previously Added) The ink jet recording apparatus as set forth in claim 84, wherein:
an annular groove is formed so as to surround the exit port, against which the annular convex is to be abutted; and ○

AMENDMENT UNDER 37 C.F.R. § 1.111
U.S. APPLICATION NO. 09/545,834
ATTORNEY DOCKET NO. Q58793

wherein an outer peripheral wall of the groove is tapered such that a diameter of thereof is reduced toward the above.

86. (Previously Added) The ink jet recording apparatus as set forth in claim 85, wherein a distance between the annular convex and the annular groove is 1.0-1.3 mm when the ink flow passage is opened. b

C1
end 87. (Previously Added) The ink jet recording apparatus as set forth in claim 81, wherein a cross sectional area of the ink flow passage between the exit port and the recording head becomes larger as further from the exit port. b

88. (Previously Added) The ink jet recording apparatus as set forth in claim 80, wherein the actuation body is a rod member arranged below the diaphragm. ✓
